






## STEEL PIPE PRODUCTS


<b>8162 Seamless Steel Pipe</b>																	
	<table border="1"> <tr> <td>Standard</td> <td>GB/T 8162—2008 ASTM106Gr.B ASTM A53Gr.B</td> </tr> <tr> <td>Material</td> <td>Q345B 20# ST35 10#, X42,X52,X60</td> </tr> <tr> <td>Diameter</td> <td>114MM--914MM</td> </tr> <tr> <td>Thickness</td> <td>4MM--60MM</td> </tr> <tr> <td>Type</td> <td>Seamless Steel Pipe</td> </tr> <tr> <td>Special pipe</td> <td>Regular and special thick-walled steel pipe, maximum thickness of up to 60MM</td> </tr> <tr> <td>Process</td> <td>Hot rolled and heat expansion</td> </tr> <tr> <td>Specification</td> <td>114--914*4--60</td> </tr> </table>	Standard	GB/T 8162—2008 ASTM106Gr.B ASTM A53Gr.B	Material	Q345B 20# ST35 10#, X42,X52,X60	Diameter	114MM--914MM	Thickness	4MM--60MM	Type	Seamless Steel Pipe	Special pipe	Regular and special thick-walled steel pipe, maximum thickness of up to 60MM	Process	Hot rolled and heat expansion	Specification	114--914*4--60
Standard	GB/T 8162—2008 ASTM106Gr.B ASTM A53Gr.B																
Material	Q345B 20# ST35 10#, X42,X52,X60																
Diameter	114MM--914MM																
Thickness	4MM--60MM																
Type	Seamless Steel Pipe																
Special pipe	Regular and special thick-walled steel pipe, maximum thickness of up to 60MM																
Process	Hot rolled and heat expansion																
Specification	114--914*4--60																

<b>8163 Seamless Steel Pipe</b>															
	<table border="1"> <tr> <td>Standards:</td> <td>GB/T 8163--2008</td> </tr> <tr> <td>Grade</td> <td>A106 A53B Q345B 20# ST35? 10#</td> </tr> <tr> <td>outer diameter</td> <td>114MM--610MM</td> </tr> <tr> <td>thickness</td> <td>4MM--60MM</td> </tr> <tr> <td>special pipe</td> <td>normal wall thickness and heavy wall thickness,the biggest thickness is 60MM:</td> </tr> <tr> <td>technique manufacture technique</td> <td>seamless hot-rolled and hot expanded</td> </tr> <tr> <td>specification</td> <td>114--610*4--60</td> </tr> </table>	Standards:	GB/T 8163--2008	Grade	A106 A53B Q345B 20# ST35? 10#	outer diameter	114MM--610MM	thickness	4MM--60MM	special pipe	normal wall thickness and heavy wall thickness,the biggest thickness is 60MM:	technique manufacture technique	seamless hot-rolled and hot expanded	specification	114--610*4--60
Standards:	GB/T 8163--2008														
Grade	A106 A53B Q345B 20# ST35? 10#														
outer diameter	114MM--610MM														
thickness	4MM--60MM														
special pipe	normal wall thickness and heavy wall thickness,the biggest thickness is 60MM:														
technique manufacture technique	seamless hot-rolled and hot expanded														
specification	114--610*4--60														

<b>PI 5L Spiral welded pipe</b>															
	<table border="1"> <tr> <td>Material</td> <td>Q235B,Q345B,X42,X52,X60</td> </tr> <tr> <td>Diameter</td> <td>219MM-1220MM</td> </tr> <tr> <td>Thickness</td> <td>6-20MM</td> </tr> <tr> <td>Type</td> <td>Spiral welded Pipe</td> </tr> <tr> <td>Process</td> <td>SAW</td> </tr> <tr> <td>Length</td> <td>12m or as your requirements</td> </tr> <tr> <td>Specification</td> <td>219-1220*6-20</td> </tr> </table>	Material	Q235B,Q345B,X42,X52,X60	Diameter	219MM-1220MM	Thickness	6-20MM	Type	Spiral welded Pipe	Process	SAW	Length	12m or as your requirements	Specification	219-1220*6-20
Material	Q235B,Q345B,X42,X52,X60														
Diameter	219MM-1220MM														
Thickness	6-20MM														
Type	Spiral welded Pipe														
Process	SAW														
Length	12m or as your requirements														
Specification	219-1220*6-20														

<b>Welded pipe</b>																	
	<table border="1"> <tr> <td>Standard:</td> <td>SY/T3091-2001</td> </tr> <tr> <td>Material:</td> <td>Q195,Q215,Q235,Q345B, X42,X52,X60</td> </tr> <tr> <td>Diameter:</td> <td>114MM—1440MM</td> </tr> <tr> <td>Thickness:</td> <td>4MM--30MM</td> </tr> <tr> <td>Type:</td> <td>Straight welded Steel Pipe</td> </tr> <tr> <td>Process:</td> <td>ERW LSAW</td> </tr> <tr> <td>Length:</td> <td>As your requirements</td> </tr> <tr> <td>Specification:</td> <td>114-1440*4-30</td> </tr> </table>	Standard:	SY/T3091-2001	Material:	Q195,Q215,Q235,Q345B, X42,X52,X60	Diameter:	114MM—1440MM	Thickness:	4MM--30MM	Type:	Straight welded Steel Pipe	Process:	ERW LSAW	Length:	As your requirements	Specification:	114-1440*4-30
Standard:	SY/T3091-2001																
Material:	Q195,Q215,Q235,Q345B, X42,X52,X60																
Diameter:	114MM—1440MM																
Thickness:	4MM--30MM																
Type:	Straight welded Steel Pipe																
Process:	ERW LSAW																
Length:	As your requirements																
Specification:	114-1440*4-30																

	<b>Spiral welded pipe</b>	
	Material:	Q235B,Q345B,X42,X52,X60
Diameter:	219MM-1220MM	
Thickness:	6-20MM	
Type:	Spiral welded Pipe	
Process:	SAW	
Length:	12m or as your requirements	
Specification:	219-1220*6-20	

	<b>Hot Expansion</b>	
	Standard:	GB/T 8162--2008
Material:	A106 A53B Q345B 20# ST35 10#, X42,X52,X60	
Diameter:	114MM--914MM	
Thickness:	4MM--60MM	
Type:	Seamless Steel Pipe	
Special pipe:	Regular and special thick-walled steel pipe, maximum thickness of up to 60MM	
Process:	Hot rolled and heat expansion	
Length:	As your requirements	
Specification:	114--914*4--60	

DIAMATER*THICKNESS (mm)	LENGTH (m)	DIAMATER*THICKNESS (mm)	LENGTH (m)
133*4-20	5.8M - 12M	141.3*6.55-19.05	5.8M 6M 12M
140*4-20	5.8M -12M	168.3*7.11-21.95	5.8M 6M 12M
159*4.5-20	5.8M - 12M	219.1*6.35-23.01	5.8M 6M 12M
168*5.5-25	5.8M - 12M	273.1*6.35-28.56	5.8M 6M 12M
180*6-25	5.8M - 12M	323.8*6.35-27.79	5.8M 6M 12M
194*6-25	5.8M - 12M	406.4*6.35-30.96	5.8M 6M 12M
219*6-30	5.8M - 12M	508*9.53-26.19	5.8M 6M 12M
245*6-30	5.8M- 12M	559*9.53-28.58	5.8M 6M 12M
273*6-30	5.8M- 12M	610*9.53-30.96	5.8M 6M 12M
325*6-30	5.8M - 12M	660*7.92-30.96	5.8M 6M 12M
356*6-30	5.8M - 12M	711*7.92-30.96	5.8M 6M 12M
377*6-30	5.8M- 12M	762*9.53-30.96	5.8M 6M 12M
406*6-30	5.8M- 12M	813*9.53-30.96	5.8M 6M 12M
426*7-30	5.8M- 12M	864*9.53-30.96	5.8M 6M 12M
480*8-30	5.8M- 12M	914*9.53-30.96	5.8M 6M 12M
508*8-35	5.8M- 12M	914*9.53-30.96	5.8M 6M 12M
530*8-35	5.8M- 12M	Petroleum Transport Pipe	5.8M 6M 12M
610*8-35	5.8M - 12M	273*7.8-28.56	5.8M 6M 12M
630-920*8-35	5.8M- 12M	323.8-610	5.8M 6M 12M